

# Engineered Materials Water Management Solutions



	Application	Product	NSF 61
Commercial Plumbing	Handles	LubriOne™ Wear Resistant Compounds	✓
	Ball Valves	Maxxam™ Polyolefin Compounds	✓
	Butterfly Valves	Maxxam™ Polyolefin Compounds	✓
	Diaphragm Valves	Nymax™ Polyamide Compounds	✓
	Check Valves	LubriOne™ Wear Resistant Compounds, Nymax™ Polyamide Compounds	✓
	Globe Valves	Nymax™ Polyamide Compounds	✓
	Gate Valves	Maxxam™ Polyolefin Compounds	✓
	Constant Flow Valves	Maxxam™ Polyolefin Compounds	✓
	Needle Valves	LubriOne™ Wear Resistant Compounds	✓
	Fittings	LubriOne™ Wear Resistant Compounds	✓
Irrigation	Pivot Heads	LubriOne™ Wear Resistant Compounds, Nymax™ Polyamide Compounds	
	Spigot Heads	LubriOne™ Wear Resistant Compounds, Nymax™ Polyamide Compounds	
	Diffusers	Maxxam™ Polyolefin Compounds	
	Flow Meters	Maxxam™ Polyolefin Compounds	
	Pressure Regulators	Maxxam™ Polyolefin Compounds	
	Strainers/Filters	Maxxam™ Polyolefin Compounds	

## NSF 61 Listed - Potable Water Materials

Platform	Trade Designation	Water Contact Temperature	Material	End Use
LubriOne™	LB4220-0001 Natural	180°F	POM	Fittings and Handles
Nymax™	600 A ZIP 39 Natural A	73.4°F	PA	Fittings and Appurtenances
Nymax™	600 A ZIP 43 Natural A	73.4°F	PA	Fittings and Appurtenances
Maxxam™	PPC-20G Natural	180°F	PP	Fittings and Appurtenances
Maxxam™	PPC-20G Black	180°F	PP	Fittings and Appurtenances
Maxxam™	PPC-30G Natural	180°F	PP	Fittings and Appurtenances
Maxxam™	PPC-30G Black	180°F	PP	Fittings and Appurtenances
Maxxam™	PPC-40G Natural	180°F	PP	Fittings and Appurtenances
Maxxam™	PPC-40G Black	180°F	PP	Fittings and Appurtenances
Maxxam™	NT-818.B001-8000	180°F	PP	Fittings and Appurtenances
Maxxam™	NT-818.B001-7001	180°F	PP	Fittings and Appurtenances

**PolyOne offers complementary and alternative material solutions for many water management applications, ranging from engineered thermoplastics and vinyl compounds and resins to thermoplastic elastomers and color and additives. For more information about how our technologies can benefit your application, please visit [www.polyone.com](http://www.polyone.com) or call 440-930-1000.**

### CONTACT INFORMATION

#### Americas

U.S. – Avon Lake OH  
+1 866 POLYONE

Brazil – Sao Paulo  
+55 11 3576 2500

Mexico – Toluca  
+52 722 2790200

#### Asia

China - Shanghai  
+86 21 5080 1188

China - Shenzhen  
+86 755 2969 2888

China - Suzhou  
+86 512 6823 24 38

India - Mumbai  
+91 22 27784426

Japan - Tokyo  
+81 369 129 102

Singapore  
+65 6861 9325

South Korea - Seoul  
+82 (2) 501-9037

**Europe**  
Czech Republic - Praha  
+420 224 142 214

France - Tossiat  
+33 474 42 69 70

Germany - Gaggenau  
+49 7225 6802 0

Italy - Gallarate  
+39 03 31 797 448

Poland - Kutno  
+48 24 357 47 00

Spain - Barbastro  
+34 974 310 314

Sweden - Angered Sales  
+46 31 928 450

Turkey - Istanbul  
+90 212 549 2256



[www.polyone.com](http://www.polyone.com)

#### PolyOne Americas

33587 Walker Road  
Avon Lake, Ohio 44012  
United States  
+1 440 930 1000

#### PolyOne Asia

Guoshoujing Road No. 88  
Z.J Hi-Tech Park, Pudong  
Shanghai, 201203, China  
+86 (0) 21 5080 1188

#### PolyOne Europe

6 Giällewee  
Fischbach, Luxembourg L-9749  
+32 (0) 83 660 211

Copyright © 2011, PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.