

MATERIAL SAFETY DATA SHEET

PANTONE RED 032C

Version Number 1.0 Revision Date 09/19/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PANTONE RED 032C
Product code	:	CC10000713
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PANTONE RED 032C

Version Number 1.0 Revision Date 09/19/2001 Page 2 of 5 Print Date 11/1/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	eek
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	: None	
	ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Here only in areas with appropriate exhaust ventilation.	ıt
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	n



MATERIAL SAFETY DATA SHEET

PANTONE RED 032C

ision Date 09/19/2001			Print	Page 3 of . Date 11/1/201	
and contamination. Keep in a dry, cool place.					
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	No personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: P	: Protective gloves.			
Skin and body protection	: L	long sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		Handle in accordance with good Vash hands before breaks and a		afety practice.	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Components Titanium dioxide	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type	List: ACGIH	
	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL:	Exposure type Total dust.	ACGIH OSHA Z1	
	10 mg/m3	Time Weighted Average (TWA):	^ * *	ACGIH	
	10 mg/m3 15 mg/m3 10 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	Total dust. as Ti	ACGIH OSHA Z1	
Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSI	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Total dust. as Ti DPERTIES	ACGIH OSHA Z1 MX OEL	
Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Total dust. as Ti DPERTIES ration rate : Not	ACGIH OSHA Z1 MX OEL applicable.	
Titanium dioxide Form Appearance	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pello	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specifi	Total dust. as Ti PERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA Z1 MX OEL applicable. determined.	
Titanium dioxide Form Appearance Color	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pello : REE	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specific D Bulk d	Total dust. as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established	
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pello : REE : Very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specifi D Bulk d / faint Vapor	Total dust. as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pelle : RED : Very : Not	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapore ets Specifie O Bulk d / faint Vapor determined. Vapor	Total dust. as Ti PERTIES ration rate : Not ration rate : Not ensity : Not pressure : Not density : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established applicable applicable	
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pelle : RED : Very : Not	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specifie y faint Vapor determined. Vapor applicable pH	Total dust. as Ti PERTIES ration rate : Not ration rate : Not ensity : Not pressure : Not density : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pella : RED : Very : Not : Not : Inso	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specifie y faint Vapor determined. Vapor applicable pH	Total dust. as Ti OPERTIES ration rate : Not c Gravity : Not ensity : Not density : Not : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established applicable applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pelle : REE : Very : Not : Not : Inso 10. S	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specifie D Bulk d / faint Vapor applicable pH luble PRO	Total dust. as Ti OPERTIES ration rate : Not c Gravity : Not ensity : Not density : Not : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established applicable applicable	
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 10 mg/m3 9. PHYSIO : Solid : Pella : RED : Very : Not : Not : Inso 10. S : S	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapor ets Specifi D Bulk d / faint Vapor determined. Vapor applicable pH luble STABILITY AND REACTIV	Total dust. as Ti OPERTIES ration rate : Not c Gravity : Not ensity : Not density : Not : Not	ACGIH OSHA Z1 MX OEL applicable. determined. established applicable applicable	



MATERIAL SAFETY DATA SHEET

PANTONE RED 032C

sion Date 09/19/2001			Print Date 11/1/2		
Incompatible Materials	: Incompatible w	ith strong acids and o	oxidizing agents.		
Hazardous decomposition products			oxide (CO), oxides of nitrogen nd smoke are all possible.		
	11. TOXICOLOGI	CAL INFORMATIO	DN		
This mixture has not been e health data for the individua <u>Toxicity Overview</u>			are effects listed are based on ex		
	ollowing components whi	ch in their pure form	have the following characteristic		
CAS-No. 13463-67-7 Tit	Chemical Name anium dioxide	Effect Systemic effects	Target OrganRespiratory system.		
	12. ECOLOGICA	L INFORMATION	I		
Persistence and degradabili					
Environmental Toxicity		-	s they are bound within the matri		
Bioaccumulation Potential		: Chemicals are not readily available as they are bound within the matrix			
Additional advice	: No data availab	No data available.			
	13. DISPOSAL C	ONSIDERATIONS			
Product	recycling is pre waste material l transportation a	ferred to disposal or the has the responsibility	t can be recycled. Where possible incineration. The generator of for proper waste classification, lance with applicable federal, S.		
Contaminated packaging	has the response and disposal in	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPOR	T INFORMATION			
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for	or transportation.			
	. Natao and the diffe	: Not regulated for transportation.			
ICAO/IATA	: Not regulated to	or transportation.			



MATERIAL SAFETY DATA SHEET

PANTONE RED 032C

Version Number 1.0 Revision Date 09/19/2001 Page 5 of 5 Print Date 11/1/2011

	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Not Listed.
China IECS	:	Listed.
Europe EINECS	:	Not Listed.
Japan ENCS	:	Not Listed.
Korea KECI	:	Not Listed.
Philippines PICCS	:	Not Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.