

MATERIAL SAFETY DATA SHEET

GOLD

Version Number 1.0 Revision Date 09/25/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GOLD
Product code	:	CC10002047
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.



MATERIAL SAFETY DATA SHEET

GOLD

sion Date 09/25/2001	Print Date 11/1/	
4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits		
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Autoignition temperature	: Not relevant	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.	
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive	
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.	
Unusual Fire/Explosion Hazards	: None	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	



MATERIAL SAFETY DATA SHEET

GOLD

sion Date 09/25/2001			Print	Page 3 Date 11/1/2
	a	nd contamination. Keep in a o	dry, cool place.	
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protect	ive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shield	5.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with goo Vash hands before breaks and		afety practice
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Mica	3 mg/m3	Time Weighted Average	Dust.	ACCILL
Mica	5 mg/m5	(TWA):	Dust.	ACGIH
	20 mppcf	• •	Dust.	OSHA
	20 mppcf	(TWA): Time Weighted Average	Dust.	
	20 mppcf 9. PHYSIC	(TWA): Time Weighted Average (TWA):	Dust.	OSHA
Form	20 mppcf	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Dust. OPERTIES oration rate : Not	
	20 mppcf 9. PHYSIC : Solic : Pelle	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO Evapore ts Species	Dust. OPERTIES pration rate : Not fic Gravity : Not	OSHA applicable.
Form Appearance	20 mppcf 9. PHYSIC : Solic : Pelle	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO the Evapore the Evapo	Dust. OPERTIES oration rate : Not fic Gravity : Not density : Not	OSHA applicable. determined.
Form Appearance Color	20 mppcf 9. PHYSIC : Solic : Pelle : YEL : Very	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapo ets Special LOW Bulk of faint Vapo	Dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not	applicable. determined. established
Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 9. PHYSIC : Solid : Pelle : YEL : Very : Not a : Not a	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRODUCT I Evapor ets Special LOW Bulk of faint Vapor Vapor determined. Vapor applicable pH	Dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not r density : Not	applicable. determined. established applicable
Form Appearance Color Odor Melting point/range	20 mppcf 9. PHYSIC : Solic : Pelle : YEL : Very : Not of	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRODUCT I Evapor ets Special LOW Bulk of faint Vapor Vapor determined. Vapor applicable pH	Dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not r density : Not	applicable. determined. established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 9. PHYSIC : Solic : Pelle : YEL : Very : Not a : Insol	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRODUCT I Evapor ets Special LOW Bulk of faint Vapor Vapor determined. Vapor applicable pH	Dust. Depending of the second	applicable. determined. established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 9. PHYSIC : Solic : Pelle : YEL : Very : Not a : Insol 10. \$	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapore ets Special LOW Bulk or r faint Vapore determined. Vapore applicable pH	Dust. Depending of the second	applicable. determined. established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	20 mppcf 9. PHYSIC : Solid : Pelle : YEL : Very : Not a : Insol 10. S : S	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRODUCTION I Evapore ets Specification LOW Bulk of of faint Vapore determined. Vapore applicable pH uble STABILITY AND REACTION	Dust. Depending of the second	applicable. determined. established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	20 mppcf 9. PHYSIC : Solic : Pelle : YEL : Very : Not c : Not c : Insol 10. S 1 . S 1 . S	(TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO CAL A	Dust. OPERTIES oration rate : Not fic Gravity : Not density : Not r pressure : Not r density : Not : Not VITY nts and open flame. To a	OSHA applicable. determined. established applicable applicable



MATERIAL SAFETY DATA SHEET

GOLD

oon dioxide (CO2), carbon mono x), other hazardous materials, an	Page 4 of Print Date <u>11/1/20</u> oxide (CO), oxides of nitrogen
x), other hazardous materials, an	
x), other hazardous materials, an	xide (CO), oxides of nitrogen
007 0 070 1 F	
COLOGICAL INFORMATIO	DN
which comprise the mixture.	are effects listed are based on exis
-	have the following characteristics
Jame Effect	Target Organ
Systemic effects	Respiratory system.
OLOGICAL INFORMATION	
readily biodegradable.	
nicals are not readily available as e polymer.	s they are bound within the matrix
nicals are not readily available as e polymer.	s they are bound within the matrix
lata available.	
SPOSAL CONSIDERATIONS	
most thermoplastics the product cling is preferred to disposal or in e material has the responsibility portation and disposal in accord /provincial and local regulations	for proper waste classification, ance with applicable federal,
ccling is preferred when possible he responsibility for proper wast disposal in accordance with appl local regulations.	· 1
ANSPORT INFORMATION	
regulated for transportation.	
regulated for transportation.	
regulated for transportation.	
r	regulated for transportation.



MATERIAL SAFETY DATA SHEET

GOLD

Version Number 1.0 Revision Date 09/25/2001 Page 5 of 5 Print Date 11/1/2011

	15	3. REGULATORY INFORMATION	
US Regulations:			
OSHA Status	:	Classified as hazardous	
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.	
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.	
Canadian Regulations:			
WHMIS Classification	:	Not controlled.	
WHMIS Ingredient Disclosure List			
CAS-No. 1333-86-4 1309-37-1 12001-26-2 150-13-0			
DSL	:	Listed.	
National Inventories:			
Australia AICS	:	Listed.	
China IECS	:	Listed.	
Europe EINECS	:	Not Listed.	
Japan ENCS	:	Not Listed.	
Korea KECI	:	Listed.	
Philippines PICCS	:	Listed.	
		16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.