9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 1 of 18 Print Date 11/17/2018

SAFETY DATA SHEET

9874 LIGHT ASH GREY NNG-02 UV

Section 1. Identification	on			
GHS product identifier Chemical name	:	9874 LIGHT ASH GREY NNG-02 UV Mixture		
CAS number Other means of identification Product type	:	Mixture CC10172909 solid		
Relevant identified uses of the substance or mixture and uses advised against				
Product use Supplier's details	:	Industrial applications. Plastics. POLYONE CORPORATION		
		33587 Walker Road, Avon Lake, OH 44012		
Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or		
(with hours of operation)	•	accident).		

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		
Signal word	:	No signal word.
		1/18

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 2 of 18 Print Date 11/17/2018

Hazard statements

No known significant effects or critical hazards.

Precautionary statements

General	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

:

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10172909

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	30 - 60	13463-67-7
2-Propenenitrile, polymer with Ethenylbenzene	30 - 60	9003-54-7
Styrene	0.1 - 1	100-42-5
Carbon black	0.1 - 1	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017

Page 3 of 18 Print Date 11/17/2018

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential	acute	health	effects
-----------	-------	--------	---------

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
C		

Over-exposure signs/symptoms

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

tolyUne.

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 4 of 18 Print Date 11/17/2018

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning up		
Small spill	:	Move containers from spill area. Vacuum or sweep up material and

me

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 5 of 18 Print Date 11/17/2018

Large spill

place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

:

Control parameters

Occupational exposure limits

OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3
PEL: Permissible Exposure Level 3.5 mg/m3
OSHA PEL (1993-06-30)
PEL: Permissible Exposure Level 3.5 mg/m3
NIOSH REL (1994-06-01)
Time Weighted Average (TWA) 3.5 mg/m3
Time Weighted Average (TWA)
ACGIH TLV (2010-12-06)
TLV-TWA: Threshold Limit Value - Time weighted average PEL:



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017

	Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction
Titanium dioxide	OSHA PEL 1989 (1989-03-01)PEL: Permissible Exposure Level 10 mg/m3 Form: Total dustOSHA PEL (1993-06-30)PEL: Permissible Exposure Level 15 mg/m3 Form: Total dustNIOSH REL (1994-06-01)ACGIH TLV (1996-05-18)TLV-TWA: Threshold Limit Value - Time weighted average PEL:Permissible Exposure Level 10 mg/m3
2-Propenenitrile, polymer with Ethenylbenzene	
Styrene	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fifteen minutes, unless otherwise stated. 425 mg/m3 100 ppm OSHA PEL Z2 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any time during any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fifteen minutes, unless otherwise stated. 425 mg/m3 100 ppm ACGIH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure Level 170 mg/m3 40 ppm
	 Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be



. 11

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2	Page 7 of 18
Revision Date 09/25/2017	Print Date 11/17/2018

		necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	: soli	d [Pellets.]
Color	: GR	EY
Odor	: Fair	nt odor.
Odor threshold	: Not	available.
рН	: Not	available.
Melting point	: Not	available.
Boiling point	: Not	available.
Flash point	: Not	available.



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 8 of 18 Print Date 11/17/2018

Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature		Not available.
SADT		Not available.
Viscosity		Dynamic: Not available.
		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017

Page 9 of 18 Print Date 11/17/2018

Styrene LD50 Oral 2,650 mg/kg Rat -LD50 Oral Rat 5,000 mg/kg _ 2,770 ppm LC50 Inhalation Rat 4 hLC50 Inhalation Rat 11.8 mg/l 4 h Carbon black LD50 Oral 15,400 mg/kg Rat -Titanium dioxide LC50 Inhalation 6.82 Mg/l Rat - Male 4 h LD50 Dermal > 5,000 mg/kg Rabbit -2-Propenenitrile, polymer with Ethenylbenzene 1,800 mg/kg LD50 Oral Rat -:

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild	Human			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes -	Rabbit		24 hrs	-
	Moderate				
	irritant				
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin		ixture.Not ful			
Eyes		ixture.Not ful			
Respiratory	: M	ixture.Not ful	ly tested.		
<u>Sensitization</u>					
Conclusion/Summary					
Skin	: M	ixture.Not ful	ly tested.		
Respiratory	: M	ixture.Not ful	ly tested.		
<u>Mutagenicity</u>					
Conclusion/Summary	: M	ixture.Not ful	ly tested.		
		9/18	5		



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 10 of 18 Print Date 11/17/2018

Carcinogenicity

Product/ingredient	OSHA	IARC	NTP
name			
Styrene		2B	Reasonably anticipated to be a human carcinogen
Carbon black		2B	
Titanium dioxide		2B	
2-Propenenitrile, polymer		3	
with Ethenylbenzene			
Reproductive toxicity			
Conclusion/Summary	:	Mixture.Not fu	lly tested.
<u>Feratogenicity</u>			
Conclusion/Summary	:	Mixture.Not fu	lly tested.
Specific target organ toxicity Not available.	<u>(single expo</u>	<u>sure)</u>	
Specific target organ toxicity Not available.	<u>(repeated ex</u>	posure)	
Aspiration hazard Not available.			
nformation on likely routes o	of :	Not available.	
-			
xposure			
xposure Potential acute health effects		No known sign	ificant effects or critical hazards
xposure <u>Potential acute health effects</u> Eye contact			ificant effects or critical hazards.
xposure otential acute health effects Eye contact nhalation	:	No known sign	ificant effects or critical hazards.
xposure Potential acute health effects Eye contact Inhalation Skin contact	:	No known sign No known sign	
xposure Potential acute health effects Eye contact Inhalation Skin contact Ingestion	:	No known sign No known sign No known sign	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards.
exposure <u>Potential acute health effects</u> Eye contact Inhalation Skin contact Ingestion <u>Symptoms related to the physi</u>	: : ical, chemica	No known sign No known sign No known sign	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards. gical characteristics
exposure <u>Potential acute health effects</u> Eye contact Inhalation Skin contact Ingestion <u>Symptoms related to the physi</u> Eye contact Inhalation	: : ical, chemica :	No known sign No known sign No known sign al and toxicolo g	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards. gical characteristics a.

PolyOne.

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 11 of 18 Print Date 11/17/2018

Ingestion	:	No specific data.
Delayed and immediate effects as v	vell as	chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects <u>Numerical measures of toxicity</u>	:::::::::::::::::::::::::::::::::::::::	No known significant effects or critical hazards. No known significant effects or critical hazards.
Acute toxicity estimates		

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Styrene			
	Acute LC50 9,900 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 9.1 mg/l Marine water	Fish - Fish	96 h
	Acute LC50 4,020 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4.7 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4,080 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 23,000 µg/l Fresh	Aquatic invertebrates.	48 h
	44/40		



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 12 of 18 Print Date 11/17/2018

	Acute EC50 19.3 mg/l Fresh water	Daphnia Aquatic invertebrates.	48 h
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates.	48 h
	Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 11 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 > 1,000 mg/l Fresh water	Fish - Fish	96 h
Trainum dioxide	Acute LC50 > 1,000,000 µg/l Marine water	Fish - Fish	96 h
Titanium dioxide	water	Daphnia	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	Acute EC50 37.563 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Carbon black	Acute NOEC 05 µg/111esii watei	Aquatic plants - Algae	4 u
	water Acute NOEC 63 µg/l Fresh water	Aquatic plants - Algae	4 d
	Acute EC50 78,000 µg/l Marine	Aquatic plants - Algae	96 h
	Acute EC50 720 µg/l Fresh water	Aquatic plants - Algae	72 h
	Acute EC50 33 mg/l Fresh water Acute EC50 720 µg/l Fresh water	Aquatic plants - Algae Aquatic plants - Algae	96 h
		Crustaceans	96 h
	Acute LC50 52 mg/l Marine water	Aquatic invertebrates.	48 h
	Acute LC50 59,000 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
		Daphnia	
	Acute EC50 4,700 µg/l Fresh water	Daphnia Aquatic invertebrates.	48 h



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017

Page 13 of 18 Print Date 11/17/2018

invertebrates.:		
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.
Persistence and degradability		
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Styrene	0.35	13.49	low
Titanium dioxide		-	low

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC) Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

ne.

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 14 of 18 Print Date 11/17/2018

Section 14. Transport information U.S.DOT 49CFR
Ground/Air/Water : Not regulated for transportation. International Air
ICAO/IATA : Not classified as dangerous goods under transport regulations.

International Water IMO/IMDG : Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations	United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
	United States - TSCA 4(a) - Final Test Rules: Not listed
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not
	listed
	United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
	United States - TSCA 8(a) - Preliminary assessment report
	(PAIR): Not listed United States TSCA 8(a) Significant advance reaction (SAR):
	United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed
	United States - EPA Clean water act (CWA) section 307 - Priority
	pollutants: Listed Rutile, antimony chromium buff
	Acrylonitrile
	United States - EPA Clean water act (CWA) section 311 -
	Hazardous substances: Listed
	United States - EPA Clean air act (CAA) section 112 - Accidental

ne

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 15 of 18 Print Date 11/17/2018

release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential	:	Not listed
Chemicals)	•	i tot listoa

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

Not applicable.

:

Composition/information on ingredients

Name	%	Classification
Styrene	0.1 - 1	F, AH, CH
Carbon black	0.1 - 1	СН
Titanium dioxide	30 - 60	СН
2-Propenenitrile, polymer with Ethenylbenzene	30 - 60	АН

SARA 313

Product name	CAS number	%
Rutile, antimony chromium	68186-90-3	5 - 10
buff		
Styrene	100-42-5	0.1 - 1
Rutile, antimony chromium	68186-90-3	5 - 10
buff		
Styrene	100-42-5	0.1 - 1
	Rutile, antimony chromium buff Styrene Rutile, antimony chromium buff	Rutile, antimony chromium buff68186-90-3Styrene100-42-5Rutile, antimony chromium buff68186-90-3

ne

9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 16 of 18 Print Date 11/17/2018

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	The following components are listed:
New Jersey	:	Styrene The following components are listed: Styrene Carbon black Iron oxide
Pennsylvania	:	Rutile, antimony chromium buff Titanium dioxide 2-Propenenitrile, polymer with Ethenylbenzene The following components are listed: Aluminum hydroxide
		Iron oxide
		Silica, amorphous
		Rutile, antimony chromium buff
		Titanium dioxide
		Styrene
		Carbon black
California Prop. 65 WARNING: This product contains a c	hemi	cal known to the State of California to cause cancer.
United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	Not determined.
Canada	:	All components are listed or exempted.
China	:	Not determined.
		16/18



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 17 of 18 Print Date 11/17/2018

Europe inventory :	All components are listed or exempted.
Japan :	Not determined.
New Zealand	Not determined.
Philippines :	Not determined.
Republic of Korea :	All components are listed or exempted.
Taiwan	All components are listed or exempted.
Turkey :	Not determined.
United States :	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.) :

Health	*	1
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

<u>History</u>		
Date of printing	:	11/17/2018
Date of issue/Date of revision	:	09/25/2017
Date of previous issue	:	10/19/2016
Version	:	1.2
Key to abbreviations	:	ATE = Acute Toxicity Estimate
-		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-

17/18



9874 LIGHT ASH GREY NNG-02 UV

Version Number 1.2 Revision Date 09/25/2017 Page 18 of 18 Print Date 11/17/2018

named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.