GREY ABS

Version Number 1.0 Revision Date 09/05/2017

ne

Page 1 of 18 Print Date 11/16/2018

SAFETY DATA SHEET

GREY ABS

Section 1. Identification	on	
GHS product identifier		GREY ABS
Chemical name	:	Mixture
CAS number		Mixture
Other means of identification		CC10258471
Product type		solid
v 1		
Relevant identified uses of the subs	stance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		
Signal word	:	No signal word.
		1/18

GREY ABS

Version Number 1.0 Revision Date 09/05/2017

Page 2 of 18 Print Date 11/16/2018

Hazard statements

No known significant effects or critical hazards.

Precautionary statements

General	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

:

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10258471

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	30 - 60	13463-67-7
2-Propenenitrile, polymer with Ethenylbenzene	10 - 30	9003-54-7
Styrene	0.1 - 1	100-42-5
Carbon black	0.1 - 1	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

GREY ABS

Version Number 1.0 Revision Date 09/05/2017

PolyOne

Page 3 of 18 Print Date 11/16/2018

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects	5
--------------------------------	---

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
-		-

Over-exposure signs/symptoms

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

GREY ABS

Version Number 1.0 Revision Date 09/05/2017 PolyOne

Page 4 of 18 Print Date 11/16/2018

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Move containers from spill area. Vacuum or sweep up material and

GREY ABS

Version Number 1.0 Revision Date 09/05/2017

PolyOne

Page 5 of 18 Print Date 11/16/2018

Large spill

place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

:

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Styrene	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 215 mg/m3 50 ppm
	Short-term exposure limit (STEL). A limit value beyond which
	there should be no exposure and which refers to a period of fifteen
	minutes, unless otherwise stated. 425 mg/m3 100 ppm
	OSHA PEL Z2 (1993-06-30)
	PEL: Permissible Exposure Level 100 ppm
	Ceiling-A concentration that should not be exceeded at any time
	during any part of the working day. 200 ppm
L	and the second s

GREY ABS



Version Number 1.0	Page 6 of 18
Revision Date 09/05/2017	Print Date 11/16/2018

	Acceptable Maximum Peak (AMP)600 ppmNIOSH REL (1994-06-01)Time Weighted Average (TWA) 215 mg/m3 50 ppmShort-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fifteen minutes, unless otherwise stated. 425 mg/m3 100 ppmACGIH TLV (1997-05-21)TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 85 mg/m3 20 ppmTLV-STEL: Threshold Limit Value - Short Time Exposure Level 170 mg/m3 40 ppm
Carbon black	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction
2-Propenenitrile, polymer with Ethenylbenzene	
Titanium dioxide	OSHA PEL 1989 (1989-03-01)PEL: Permissible Exposure Level 10 mg/m3 Form: Total dustOSHA PEL (1993-06-30)PEL: Permissible Exposure Level 15 mg/m3 Form: Total dustNIOSH REL (1994-06-01)ACGIH TLV (1996-05-18)TLV-TWA: Threshold Limit Value - Time weighted average PEL:Permissible Exposure Level 10 mg/m3
Appropriate engineering controls : Environmental exposure controls :	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

GREY ABS

Version Number 1.0 Revision Date 09/05/2017

<u>PolyOne</u>

Page 7 of 18 Print Date 11/16/2018

Individual protection measures		
Hygiene measures Eye/face protection	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.)
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.	
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. 	
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.	

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Pellets.]
Color	:	GREY
Odor	:	Faint odor.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.

GREY ABS

Version Number 1.0 Revision Date 09/05/2017 <u>PolyOne</u>

Page 8 of 18 Print Date 11/16/2018

Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
Styrene					
	LD50 Oral	Rat	2,650 mg/kg	-	



GREY ABS

Version Number	er 1.0
Revision Date	09/05/2017

Page 9 of 18 Print Date 11/16/2018

	LD50 Oral	Rat	5,000 mg/kg	-
	LC50 Inhalation	Rat	2,770 ppm	4 h
	LC50 Inhalation	Rat	11.8 mg/l	4 h
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-
2-Propenenitrile, polymer with	h Ethenylbenzene			
	LD50 Oral	Rat	1,800 mg/kg	-
Titanium dioxide		·		
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Conclusion/Summony	. Mixtu	ra Not fully tastad		

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild irritant	Human			-
	Skin - Mild	Rabbit	_		
	irritant	Kabbit			-
	Skin -	Rabbit			
	Moderate	Kabbit			-
	irritant				
		D-114			
	Eyes - Severe	Rabbit			-
	irritant	D 111		241	
	Eyes -	Rabbit		24 hrs	-
	Moderate				
	irritant				
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin		ixture.Not fu			
Eyes		ixture.Not fu			
Respiratory	: M	ixture.Not fu	lly tested.		
Sensitization					
Conclusion/Summary					
Skin	: M	ixture.Not fu	lly tested.		
Respiratory	: M	ixture.Not fu	lly tested.		
<u>Mutagenicity</u>					
Conclusion/Summary	: M	ixture.Not fu	lly tested.		
Carcinogenicity					



GREY ABS

Version Numbe	er 1.0
Revision Date	09/05/2017

Page 10 of 18 Print Date 11/16/2018

Product/ingredient	OSHA	IARC	NTP
name Styrene		2B	Reasonably anticipated to be a human carcinogen
Carbon black		2B 2B	
2-Propenenitrile, polymer with Ethenylbenzene		3	
Titanium dioxide		2B	
Reproductive toxicity			
Conclusion/Summary	:	Mixture.Not fu	lly tested.
<u>Feratogenicity</u>			
Conclusion/Summary	:	Mixture.Not fu	lly tested.
Specific target organ toxicity Not available.	(single expo	<u>sure)</u>	
Specific target organ toxicity Not available.	(repeated ex	posure)	
Aspiration hazard Not available.			
nformation on likely routes o	of :	Not available.	
xposure			
•			
otential acute health effects	:	No known sign	ificant effects or critical hazards.
otential acute health effects Eye contact			ificant effects or critical hazards. ificant effects or critical hazards.
otential acute health effects Cye contact nhalation	:	No known sign	
<u>otential acute health effects</u> Eye contact Inhalation Skin contact	:	No known sign No known sign	ificant effects or critical hazards.
Potential acute health effects Eye contact Inhalation Skin contact Ingestion	:	No known sign No known sign No known sign	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards.
Yotential acute health effects Eye contact Inhalation Skin contact Ingestion ymptoms related to the phys	: : ical, chemic:	No known sign No known sign No known sign al and toxicolo ;	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards. gical characteristics
Potential acute health effects Eye contact Inhalation Skin contact Ingestion	: : ical, chemic: :	No known sign No known sign No known sign al and toxicolog No specific dat	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards. gical characteristics a.
Yotential acute health effects Eye contact Inhalation Skin contact Ingestion <u>ymptoms related to the phys</u> Eye contact	: : ical, chemic: : :	No known sign No known sign No known sign al and toxicolo ;	ificant effects or critical hazards. ificant effects or critical hazards. ificant effects or critical hazards. gical characteristics a. a.

GREY ABS

Version Number 1.0 Revision Date 09/05/2017 PolyOne

Page 11 of 18 Print Date 11/16/2018

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Styrene			
	Acute LC50 9,900 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 9.1 mg/l Marine water	Fish - Fish	96 h
	Acute LC50 4,020 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4.7 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4,080 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 23,000 µg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute EC50 4,700 µg/l Fresh water	Aquatic invertebrates.	48 h
	11/18		



GREY ABS

Version Number 1.0 Revision Date 09/05/2017 Page 12 of 18 Print Date 11/16/2018

		Daphnia	
	Acute LC50 59,000 µg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	10 11
	Acute LC50 52 mg/l Marine water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute EC50 33 mg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 720 µg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 1,400 µg/l Fresh water	Aquatic plants - Algae	72 h
	Acute EC50 78,000 µg/l Marine	Aquatic plants - Algae	96 h
	water		
	Acute NOEC 63 µg/l Fresh water	Aquatic plants - Algae	4 d
Carbon black	· · · ·		
	Acute EC50 37.563 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Titanium dioxide			<u>.</u>
	Acute LC50 > 1,000,000 µg/l	Fish - Fish	96 h
	Marine water		
	Acute LC50 > 1,000 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	10.1
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	10.1
	Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	40.1
	Acute LC50 11 mg/l Fresh water	Aquatic invertebrates.	48 h
	A surte L C50 12 4 sec /l Erech sustan	Crustaceans	48 h
	Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 n
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates.	48 h
	Acute EC50 27.0 mg/1 Fresh water	Daphnia	+0 11
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates.	48 h
	reate LC50 17.5 mg/1110m water	Daphnia	70 11
	Acute EC50 35.306 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	10 11
GREY ABS	mutor	Dupinnu	1
Remarks - Acute - Aquatic	Chemicals are not readily available a	s they are bound within the	nolymer matrix
invertebrates.:			porymer maura.
Conclusion/Summary	Chemicals are not readil	y available as they are bou	nd within the
Conclusion Summary	12/18	j available as they are bou	

GREY ABS

<u>PolyOne</u>

Version Number 1.0 Revision Date 09/05/2017

Page 13 of 18 Print Date 11/16/2018

		polymer matrix.
Persistence and degradability		
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulative potential

Diouccumulative potentia			
Product/ingredient name	LogPow	BCF	Potential
Styrene	0.35	13.49	low
Titanium dioxide		-	low

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

contact with soil, waterways, drains and sewers.
--

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information



GREY ABS

Version Number 1.0 Revision Date 09/05/2017		Page 14 of 18 Print Date 11/16/2018
U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	:	Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations	: United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
	1
	United States - TSCA 4(a) - Final Test Rules: Not listed
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not listed
	United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not
	determined
	United States - TSCA 8(a) - Preliminary assessment report
	(PAIR): Not listed
	United States - TSCA 8(c) - Significant adverse reaction (SAR):
	Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed
	United States - EPA Clean water act (CWA) section 307 - Priority
	pollutants: Listed Acrylonitrile
	Chromium (III) oxide
	Rutile, antimony chromium buff
	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)
	United States - EPA Clean water act (CWA) section 311 -
	Hazardous substances: Listed
	United States - EPA Clean air act (CAA) section 112 - Accidental
	release prevention - Flammable substances: Not listed
	4.4/4.0

GREY ABS

Version Number 1.0 Revision Date 09/05/2017



Page 15 of 18 Print Date 11/16/2018

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II		Not listed
Substances	•	
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: Not applicable.

Composition/information on ingredients

Name	%	Classification
Styrene	0.1 - 1	F, AH, CH
Carbon black	0.1 - 1	СН
2-Propenenitrile, polymer with Ethenylbenzene	10 - 30	AH
Titanium dioxide	30 - 60	СН

SARA 313

	Product name	CAS number	%	
Form R - Reporting requirements	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	1 - 5	
	Styrene	100-42-5	0.1 - 1	
Supplier notification	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	1 - 5	

GREY ABS

Version Number 1.0 Revision Date 09/05/2017

<u>PolyOne</u>

Page 16 of 18 Print Date 11/16/2018

S	tyrene	;	100-42-5	0.1 - 1
SARA 313 notifications must not be include copying and redistribution of				
State regulations				
Massachusetts	:	None of the compone		
New York	:	The following compo	onents are listed:	
New Jersey	:	Styrene The following compo Titanium dioxide 2-Propenenitrile, po Nickel antimony ye Carbon black Styrene	lymer with Etheny	
Pennsylvania	:	The following compo Styrene	onents are listed:	
		Silica, amorphous		
		Nickel antimony ye	llow rutile (C.I. Pi	gment Yellow 53)
		Titanium dioxide		
		Carbon black		
		Aluminum hydroxi	de	
<u>California Prop. 65</u> WARNING: This product contains a	chemi	ical known to the State	of California to ca	use cancer.
United States inventory (TSCA 8b)) :	All components are	isted or exempted.	
Canada inventory	:	All components are	listed or exempted.	
International regulations				
<u>Inventory list</u>				
Australia Canada China Europe inventory Japan	:	All components are All components are All components are All components are Not determined.	listed or exempted listed or exempted	

16/18



GREY ABS

Version Number 1.0 Revision Date 09/05/2017 Page 17 of 18 Print Date 11/16/2018

New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.) :

Health	*	1
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

History

History		
Date of printing	:	11/16/2018
Date of issue/Date of revision	:	09/05/2017
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the

<u>olyUne</u>.

GREY ABS

Version Number 1.0 Revision Date 09/05/2017 Page 18 of 18 Print Date 11/16/2018

sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.