

## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 1 of 18 Print Date 09/25/2018

# SAFETY DATA SHEET

#### IR BLOCKING ACETAL V2

## **Section 1. Identification**

**GHS product identifier** : IR BLOCKING ACETAL V2

Chemical name: MixtureCAS number: MixtureOther means of identification: CC10290807

**Product type** : solid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

CARCINOGENICITY - Category 1A

**GHS label elements** 



## IR BLOCKING ACETAL V2

Version Number 1.0 Page 2 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

Hazard pictograms

Signal word : Danger

**Hazard statements** : May cause cancer.

**Precautionary statements** 

**General** : Not applicable.

**Prevention**: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves.

Wear eye or face protection. Wear protective clothing.

**Response** : IF exposed or concerned: Get medical attention.

**Storage** : Store locked up.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Supplemental label elements** : None known. **Hazards not otherwise classified** : None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC10290807

## **CAS** number/other identifiers

Ingredient name	%	CAS number
Nickel	1 - 3	7440-02-0
Nickel iron chromite black spinel (C.I. Pigment Black 30)	1 - 3	71631-15-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



### IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 3 of 18 Print Date 09/25/2018

## Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms



### IR BLOCKING ACETAL V2

Version Number 1.0 Page 4 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Firefighting measures

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or  $CO_2$ .

: None known.

Specific hazards arising from the

chemical

Hazardous thermal decomposition products

No specific fire or explosion hazard.

: If overheated or burnt, the polymer releases formaldehyde. Decomposition products may include the following materials:

nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.



## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 5 of 18 Print Date 09/25/2018

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Avoid dust generation. Do not dry

sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed

waste disposal contractor.

**Large spill**: Move containers from spill area. Approach release from upwind.

Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13

for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures**: Put on appropriate personal protective equipment (see Section 8).

Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material,



## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 6 of 18 Print Date 09/25/2018

Advice on general occupational hygiene

kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

## Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Nickel	ACGIH TLV (1998-09-01) TWA 1.5 mg/m3 Form: Inhalable fraction OSHA PEL (1993-06-30) TWA 1 mg/m3 (as Ni) NIOSH REL (2010-09-01) TWA 0.015 mg/m3 (as Ni) OSHA PEL 1989 (1989-03-01) TWA 1 mg/m3 (as Ni)
Nickel iron chromite black spinel (C.I. Pigment Black 30)	OSHA PEL (1993-06-30) TWA 1 mg/m3 (as Ni) OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m3 (as Ni) Form: Soluble ACGIH TLV (1998-09-01) TWA 0.1 mg/m3 (as Ni) Form: Inhalable fraction OSHA PEL (1993-06-30) TWA 1 mg/m3 (as Ni) OSHA PEL 1989 (1989-03-01) TWA 1 mg/m3 (as Ni)

6/18



## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 7 of 18 Print Date 09/25/2018

**Appropriate engineering controls** 

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

**Hand protection** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper



## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 8 of 18 Print Date 09/25/2018

fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

solid [Pellets.] Physical state Color NO PIGMENT Odor Not available. Not available. **Odor threshold** Not available. Not available. **Melting point Boiling point** Not available. Not available. Flash point **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

**Possibility of hazardous reactions**: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Maintain polymer temperature below 230°C (446°F). Avoid

prolonged exposure at or above recommended processing temperature.

**Incompatible materials**: Incompatible with strong oxidizers and with strong acids and bases



#### IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 9 of 18 Print Date 09/25/2018

(decomposes to form formaldehyde). At melt temperatures, acetal resins are incompatible with halogenated polymers such as vinyl (PVC) and any elastomers containing any halogenated polymers. At processing conditions, these materials are mutually destructive and involve rapid degradation. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume well above threshold levels are a likely result. Unsafe pressurization of equipment such as extruder or mold can also result. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of halogenated materials from coming in contact with the acetal. Prevent contamination of virgin or rework resin.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## **Information on toxicological effects**

#### **Acute toxicity**

Remarks - Oral:	No applicable toxicity data
Remarks - Inhalation:	No applicable toxicity data
Remarks - Dermal:	No applicable toxicity data
Remarks - Oral:	No applicable toxicity data
Remarks - Inhalation:	No applicable toxicity data
Remarks - Dermal:	No applicable toxicity data

**Conclusion/Summary** : Mixture.Not fully tested.No results available.

#### **Irritation/Corrosion**

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.

**Respiratory** : Mixture.

Sensitization

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.



## IR BLOCKING ACETAL V2

Version Number 1.0 Page 10 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

**Mutagenicity** 

**Conclusion/Summary** : Mixture. Not fully tested.

**Carcinogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Nickel		2B	Reasonably anticipated to be a human carcinogen.
Nickel iron chromite		1	
black spinel (C.I. Pigment			
Black 30)			

## **Reproductive toxicity**

Conclusion/Summary : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

**Specific target organ toxicity (single exposure)** 

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.



## IR BLOCKING ACETAL V2

Version Number 1.0 Page 11 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### **Long term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

## Potential chronic health effects

**Conclusion/Summary**: Mixture.Not fully tested.No results available.

**General**: No known significant effects or critical hazards.

**Carcinogenicity**: May cause cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### Numerical measures of toxicity

## **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Nickel			
	Acute LC50 0.000048 Mg/l Fresh	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		



## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 12 of 18 Print Date 09/25/2018

	Acute EC50 1 Mg/l Marine water	Aquatic invertebrates.	48 h
		Daphnia	
Remarks - Acute - Aquatic invertebrates.:	Acute		
invertebrates	Acute IC50 0.31 Mg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	46 11
Remarks - Acute - Aquatic	Acute		
invertebrates.:		T	<b>T</b>
	Acute EC50 2 Mg/l Marine water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Acute		
	Acute EC50 0.45 Mg/l Fresh water	Aquatic plants -	96 h
	Troute Book of the ring 1110str whiter	Aquatic plants	7011
Remarks - Acute - Aquatic	Acute	11 F	
plants:			
•	Acute NOEC 100 Mg/l Marine	Aquatic plants - Algae	72 h
	water		
Remarks - Acute - Aquatic	Chronic		•
plants:			
	Chronic NOEC 0.0035 Mg/l Fresh	Fish - Fish	28 d
	water		
Remarks - Chronic - Fish:	Chronic		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Nickel iron chromite black spir	,		
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
IR BLOCKING ACETAL V2			
Remarks - Acute - Aquatic	Chemicals are not readily available a	s they are bound within the	polymer matrix.
invertebrates.:		71.11 .1 .1	1 '4' 4

Conclusion/Summary

: Chemicals are not readily available as they are bound within the polymer matrix.

## Persistence and degradability

Conclusion/Summary

: Chemicals are not readily available as they are bound within the polymer matrix.



#### IR BLOCKING ACETAL V2

Version Number 1.0 Page 13 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

**Conclusion/Summary**: Chemicals are not readily available as they are bound within the

polymer matrix.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Nickel	-	5,613.00	high

#### **Mobility in soil**

**Soil/water partition coefficient** 

(KOC)

Not available.

Other adverse effects

No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

<u>United States - RCRA Acute hazardous waste "P" List:</u> Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## **Section 14. Transport information**

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air : Consult mode specific transport rules

13/18



#### IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 14 of 18 Print Date 09/25/2018

ICAO/IATA

International Water

IMO/IMDG

: Consult mode specific transport rules

# Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Nickel iron chromite black spinel (C.I.

Pigment Black 30) Chromium

Cnromium Nickel

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed



## IR BLOCKING ACETAL V2

Version Number 1.0 Revision Date 09/24/2018 Page 15 of 18 Print Date 09/25/2018

Clean Air Act Section 112(b) : Listed

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I : Not listed

**Substances** 

Clean Air Act Section 602 Class II : Not listed

**Substances** 

**DEA List I Chemicals (Precursor**: Not listed

**Chemicals**)

**DEA List II Chemicals (Essential**: Not listed

**Chemicals**)

## US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Nickel	7440-02-0	100 lb(s)
		45.4 kg
		_

## **SARA 311/312**

Classification : Delayed (chronic) health hazard

## **Composition/information on ingredients**

Name	%	Classification
Nickel	1 - 3	СН
Nickel iron chromite black spinel (C.I. Pigment Black 30)	1 - 3	СН

## **SARA 313**

	Product name	CAS number	%
Form R - Reporting	Nickel	7440-02-0	1 - 3
requirements			
	Chromium	7440-47-3	1 - 3
	Nickel iron chromite black spinel (C.I. Pigment Black 30)	71631-15-7	1 - 3
Supplier notification	Nickel	7440-02-0	1 - 3
	Chromium	7440-47-3	1 - 3
	Nickel iron chromite black	71631-15-7	1 - 3



## IR BLOCKING ACETAL V2

Version Number 1.0 Page 16 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

spinel (C.I. Pigment Black 30)

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts: None of the components are listed.New York: The following components are listed:

Chromium Nickel

**New Jersey** : The following components are listed:

Nickel iron chromite black spinel (C.I. Pigment Black 30)

Chromium Nickel

**Pennsylvania** : The following components are listed:

Nickel iron chromite black spinel (C.I. Pigment Black 30)

Nickel

Chromium

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

**International regulations** 

**Inventory list** 

Australia: All components are listed or exempted.Canada: All components are listed or exempted.China: All components are listed or exempted.Europe inventory: All components are listed or exempted.

Japan : Not determined.

New ZealandAll components are listed or exempted.PhilippinesAll components are listed or exempted.Republic of KoreaAll components are listed or exempted.TaiwanAll components are listed or exempted.

**Turkev** : Not determined.

**United States** : All components are listed or exempted.



#### IR BLOCKING ACETAL V2

Version Number 1.0 Page 17 of 18 Revision Date 09/24/2018 Print Date 09/25/2018

## Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**

Health	*	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**History** 

Date of printing: 09/25/2018Date of issue/Date of revision: 09/24/2018Date of previous issue: 00/00/0000

Version : 1.0

**Key to abbreviations**: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

 $IMDG = International \ Maritime \ Dangerous \ Goods$ 

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

## Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.



# IR BLOCKING ACETAL V2

 Version Number 1.0
 Page 18 of 18

 Revision Date 09/24/2018
 Print Date 09/25/2018