

GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018

Page 1 of 18 Print Date 05/12/2018

SAFETY DATA SHEET

GEON BOLD L5500 GRAY (6C)

Section 1. Identification

GHS product identifier GEON BOLD L5500 GRAY (6C)

Chemical name Mixture CAS number Mixture Other means of identification VC10012187

Product type solid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

POLYONE CORPORATION Supplier's details

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. All ingredients are bound in a PVC polymer matrix and potential for hazardous exposure as shipped is minimal. PVC resin is manufactured from Vinyl Chloride Monomer (VCM). PVC resin manufacturers take special efforts to strip residual VCM from their resins. Residual VCM in the resin is typically below 8.5 ppm. However, VCM is a known carcinogen. The end-user (fabricator) should take necessary precautions (mechanical ventilation, local exhaust, respiratory protection, etc.) to protect employees from exposure to any vapors or dusts that may be released during heating or fabrication. See Sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status While this material is not considered hazardous by the OSHA Hazard

> Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and

other users of this product.

Classification of the substance or

mixture

Not classified.

GHS label elements



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 2 of 18 Revision Date 05/11/2018 Print Date 05/12/2018

Signal word : No signal word.

Hazard statements: No known significant effects or critical hazards.

Precautionary statements

General:Not applicable.Prevention:Not applicable.Response:Not applicable.Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: VC10012187

CAS number/other identifiers

Ingredient name	%	CAS number
2-Propenenitrile, polymer with Ethenylbenzene	10 - 25	9003-54-7
Titanium dioxide	5 - 10	13463-67-7
Paraffin waxes and Hydrocarbon waxes	1 - 3	8002-74-2
Styrene	0 - 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 3 of 18 Revision Date 05/11/2018 Print Date 05/12/2018

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.

Get medical attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 4 of 18 Print Date 05/12/2018

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO_2 .

None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

No specific fire or explosion hazard.

: May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel :

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 5 of 18 Print Date 05/12/2018

or air).

Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and

place in a designated, labeled waste container. Dispose of via a

licensed waste disposal contractor.

Large spill : Move containers from spill area. Prevent entry into sewers, water

courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Advice on general occupational

hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Styrene	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 215 mg/m3 50 ppm
	Short-term exposure limit (STEL). A limit value beyond which
	there should be no exposure and which refers to a period of fifteen



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 6 of 18 Print Date 05/12/2018

	minutes, unless otherwise stated. 425 mg/m3 100 ppm OSHA PEL Z2 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any time during any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fifteen minutes, unless otherwise stated. 425 mg/m3 100 ppm ACGIH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure Level 170 mg/m3 40 ppm
Paraffin waxes and Hydrocarbon waxes	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 2 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 Form: Fume ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m3 Form: Fume
Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust NIOSH REL (1994-06-01) ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
2-Propenenitrile, polymer with Ethenylbenzene	

Appropriate engineering controls

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers,

filters or engineering modifications to the process equipment will be



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 7 of 18 Print Date 05/12/2018

necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products

if a risk assessment indicates this is necessary.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : solid [Pellets.]

Color: GREYOdor: Not available.Odor threshold: Not available.

pH
Melting point
Boiling point
Flash point
Not available.
Not available.
Not available.
Not available.



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 8 of 18 Revision Date 05/11/2018 Print Date 05/12/2018

Burning time: Not available.Burning rate: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : Not available.
Solubility : Not available.
Solubility in water : Not available.
Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Styrene				



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 9 of 18 Print Date 05/12/2018

	LD50 Oral	Rat	2,650 mg/kg	-	
	LC50 Inhalation	Rat	2,770 ppm	4 h	
	LC50 Inhalation	Rat	11.8 Mg/l	4 h	
Remarks - Dermal:	No applicable toxic	city data			
Paraffin waxes and Hydrocarbo	on waxes				
	LD50 Oral	Rat	2,000 mg/kg	-	
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxic	city data			
Titanium dioxide					
Remarks - Oral:	No applicable toxic	city data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	=	
2-Propenenitrile, polymer with	2-Propenenitrile, polymer with Ethenylbenzene				
	LD50 Oral	Rat	1,800 mg/kg	=	
Remarks - Inhalation:	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data				

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild irritant	Human			-
	Skin - Mild irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit			-
	Eyes - Severe irritant	Rabbit			-
	Eyes - Moderate irritant	Rabbit		24 hrs	-
Paraffin waxes and Hydrocarbon waxes	Skin - Moderate irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit			-
	Skin - Mild irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit		24 hrs	-
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 10 of 18 Revision Date 05/11/2018 Print Date 05/12/2018

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Classification			
Product/ingredient	OSHA	IARC	NTP
name			
Styrene		2B	Reasonably anticipated to be a human carcinogen.
Titanium dioxide		2B	
2-Propenenitrile, polymer		3	
with Ethenylbenzene			

Reproductive toxicity

Conclusion/Summary: Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of

exposure

Not available.



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 11 of 18 Revision Date 05/11/2018 Print Date 05/12/2018

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 12 of 18 Print Date 05/12/2018

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Styrene			
	Acute LC50 4.02 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 0.0047 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute LC50 52 Mg/l Marine water	Aquatic invertebrates.	48 h
		Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:	FG50 1 4 N 4 F 1	T	T 70.1
	Acute EC50 1.4 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic	Acute		
plants:	A	A	96 h
D 1 4 4 4 4	Acute EC50 0.72 Mg/l Fresh water	Aquatic plants - Algae	96 n
Remarks - Acute - Aquatic	Acute		
plants:	Aguta NOEC 0.062 Mg/l Frash	Aquatic plants - Algae	96 h
	Acute NOEC 0.063 Mg/l Fresh water	Aquatic plants - Algae	90 11
Remarks - Acute - Aquatic	Chronic		
plants:	Chrome		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:	are approximate contact, and		
Paraffin waxes and Hydrocarb	on waxes		
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Titanium dioxide			
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute	1	T
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 13 of 18 Print Date 05/12/2018

	I	T a	
		Crustaceans	
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
2-Propenenitrile, polymer with			
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
GEON BOLD L5500 GRAY ((6C)		
Remarks - Acute - Aquatic	tic Chemicals are not readily available as they are bound within the polymer matrix.		
invertebrates.:			
Complete Complete	C1	lri ariailabla aa thari ana hai	1 '.1 ' .1

Conclusion/Summary

: Chemicals are not readily available as they are bound within the polymer matrix.

Persistence and degradability

Conclusion/Summary

: Chemicals are not readily available as they are bound within the

polymer matrix.

Conclusion/Summary

: Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Benzene, ethenyl-	0.35	13.49	low

Mobility in soil



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 14 of 18 Print Date 05/12/2018 Revision Date 05/11/2018

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

Consult mode specific transport rules

International Water IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 15 of 18 Print Date 05/12/2018

United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

United States - TSCA 6 - Final risk management: Not listed

United States - TSCA 6 - Proposed risk management: Not listed

United States - TSCA 8(a) - Chemical risk rules: Not listed

United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed

United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Cyclohexene, 4-ethenyl-

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed

United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Rutile, antimony chromium buff

Phthalocyanine Blue

Acrylonitrile

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

emicals (Essential : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Page 16 of 18 Revision Date 05/11/2018 Print Date 05/12/2018

not applicable

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

Name	%	Classification
Styrene	0 - 0.3	F, AH, CH
Paraffin waxes and Hydrocarbon waxes	1 - 3	АН
Titanium dioxide	5 - 10	СН
2-Propenenitrile, polymer with Ethenylbenzene	10 - 25	АН

SARA 313

	Product name	CAS number	%
Form R - Reporting	Styrene	100-42-5	0 - 0.3
requirements			
Supplier notification	Styrene	100-42-5	0 - 0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

MassachusettsNone of the components are listed.New YorkThe following components are listed:

Styrene

New Jersey : The following components are listed:

Ethene, chloro-, homopolymer

2-Propenenitrile, polymer with Ethenylbenzene

Titanium dioxide

Paraffin waxes and Hydrocarbon waxes

Styrene

Pennsylvania : The following components are listed:

Titanium dioxide

Paraffin waxes and Hydrocarbon waxes

Styrene



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 17 of 18 Print Date 05/12/2018

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

AustraliaAll components are listed or exempted.CanadaAll components are listed or exempted.ChinaAll components are listed or exempted.Europe inventoryAll components are listed or exempted.

Japan : Not determined.

New Zealand: All components are listed or exempted.Philippines: All components are listed or exempted.Republic of Korea: All components are listed or exempted.Taiwan: All components are listed or exempted.

Turkey : Not determined.

United States : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 05/12/2018Date of issue/Date of revision: 05/11/2018Date of previous issue: 00/00/0000



GEON BOLD L5500 GRAY (6C)

Version Number 1.0 Revision Date 05/11/2018 Page 18 of 18 Print Date 05/12/2018

Version : 1.0

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.