

0 50100WOA Oasis™ Retarder

Wilflex™ Oasis Retarder is an additive designed to extend the screen life of Oasis inks.

Highlights

- ▶ Extends the screen life of Oasis inks helping to prevent ink drying in the screen.

Printing Tips

- ▶ Recommended for use with Oasis inks at a rate of 1%, up to 3% max by weight. Additions above 3% may reduce wash fastness of the print.
- ▶ Refer to Oasis base PIB.

Compliance

- ▶ Non-PVC, non-phthalate.
- ▶ For compliance certifications, please visit www.wilflex.com/compliance.

Precautions


- ▶ Most substrates are suitable for printing; however, fibers which possess a low surface adhesion (e.g. polypropylene, silk, polyamide or wool) will require special care during drying and cure processes. Test all fabrics for color fixation and wash fastness before starting any production runs.
- ▶ Perform fusion tests before production. Failure to cure ink properly may result in poor wash fastness, inferior adhesion and unacceptable durability. Ink flash temperatures should be measured on the ink surface using an infrared thermometer sensor. Ink cure temperatures should be measured using a Thermoprobe placed directly in the wet ink film (printed) and verified on the production run substrate(s) and production equipment. It is the responsibility of the printer to determine that the correct ink has been selected for a specific substrate and the application processes meet your customer's standards or specifications.
- ▶ To avoid ink interaction in the image area, verify that the screen mesh is clean of previous ghost images. The image area must be clean and de-hazed.
- ▶ Excess additions of Oasis additives into Oasis inks may adversely affect ink properties.
- ▶ Containers must maintain air-tight seal when not in use.
- ▶ **NON-CONTAMINATION OF OASIS INKS:** Do not add or mix non-Oasis inks, additives or extenders with Oasis inks. All buckets, palette knives, stirring apparatus, squeegees, flood bars and screens must be cleaned properly and free of phthalates and PVC containing inks. Non-phthalate emulsions and pallet adhesives must be used. Failure to follow these precautions may cause phthalate contamination in violation of consumer protection laws and regulations.
- ▶ Any application not referred in this product information bulletin should be pre-tested or consultation sought with Wilflex Technical Services Department prior to printing.
- ▶ Email: techserviceswilflex@polyone.com

Opacity N/A
Bleed Resistance N/A
Smooth Surface N/A
Flash N/A
Gloss N/A
Printability N/A

*Values listed 1-9, with 9 being the best rating.




Fabric Types
Refer to Oasis base PIB.



Mesh
Counts: Refer to Oasis base PIB.
Tension: Refer to Oasis base PIB.



Squeegee
Durometer: Refer to Oasis base PIB.
Edge: Refer to Oasis base PIB.
Stroke: Refer to Oasis base PIB.
Angle: Refer to Oasis base PIB.
**Do not use excess squeegee pressure.*



Water-Resistant Stencil
Direct: Refer to Oasis base PIB.
Capillary/Thick Film: N/A
Off Contact: Refer to Oasis base PIB.
Emulsion-over-Mesh: Refer to Oasis base PIB.



Flash & Cure Temperatures
Flash: Refer to Oasis base PIB.
Cure: Refer to Oasis base PIB.



Pigment Loading
WPC: N/A
**All percentages listed at % by weight.*



Oasis Additives
Add into Oasis inks at a rate of 1%.
Do not exceed 3% max.
**All percentages listed at % by weight.*



Storage
37-104°F (3-40°C)
Use within one year of manufacture date.
Keep containers sealed at all times.



Clean Up
Warm Soap Water (Tap)
Gentle Pressure



Health & Safety
MSDS: www.polyone.com or
Contact your local CSR.