YELLOW K100

Version Number 1.0 Revision Date 04/08/2020

ne

Page 1 of 17 Print Date 04/09/2020

SAFETY DATA SHEET

YELLOW K100

Section 1. Identification	n	
GHS product identifier	:	YELLOW K100
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	CC10323326
Product type	:	solid
Relevant identified uses of the subs	tance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	CARCINOGENICITY - Category 1A
GHS label elements		

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020

PolyOne

Page 2 of 17 Print Date 04/09/2020

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	May cause cancer.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.
Response	:	IF exposed or concerned: Get medical attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.
		Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10323326

CAS number/other identifiers

Ingredient name	%	CAS number
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	5 - 10	8007-18-9
Titanium dioxide	5 - 10	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020



Page 3 of 17 Print Date 04/09/2020

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020 Page 4 of 17 Print Date 04/09/2020

<u>tyUne</u>.

Over-exposure signs/symptoms

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Specific treatments	ma me	case of inhalation of decomposition products in a fire, symptoms by be delayed. The exposed person may need to be kept under dical surveillance for 48 hours.
Protection of first-aiders	sui res apj mo	action shall be taken involving any personal risk or without table training. If it is suspected that fumes are still present, the cuer should wear an appropriate mask or self-contained breathing paratus. It may be dangerous to the person providing aid to give puth-to-mouth resuscitation. Wash contaminated clothing proughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	If overheated or burnt, the polymer releases formaldehyde. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020 <u>PolyOne</u>

Page 5 of 17 Print Date 04/09/2020

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate

YELLOW K100



Version Number 1.0 Revision Date 04/08/2020	Page 6 of 17 Print Date 04/09/2020
Advice on general occupational hygiene	 ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	OSHA PEL 1989 (1989-03-01) TWA 1 mg/m3 (as Ni) OSHA PEL (1993-06-30) TWA 1 mg/m3 (as Ni) ACGIH TLV (1998-09-01) TWA 0.2 mg/m3 (as Ni) Form: Inhalable fraction

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process

YELLOW K100



Version Number 1.0 Revision Date 04/08/2020	Page 7 of 17 Print Date 04/09/2020
Environmental exposure controls	 enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety
Eye/face protection	 showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020

<u>PolyOne</u>

Page 8 of 17 Print Date 04/09/2020

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Pellets.]
Color	:	YELLOW
Odor	:	Not available.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available. Kinematic: Not available.
Aerosol product		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	-	Not available.
equivalent	•	Not available.
Enclosed space ignition -	:	Not available.
Deflagration density	•	rot uvunuoio.
Flame height	:	Not available.
Flame duration		Not available.
	:	

Section 10. Stability and reactivity

YELLOW K100



Version Number 1.0	Page 9 of 17
Revision Date 04/08/2020	Print Date 04/09/2020

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Maintain polymer temperature below 230°C (446°F). Avoid prolonged exposure at or above recommended processing temperature.
Incompatible materials	:	Incompatible with strong oxidizers and with strong acids and bases (decomposes to form formaldehyde). At melt temperatures, acetal resins are incompatible with halogenated polymers such as vinyl (PVC) and any elastomers containing any halogenated polymers. At processing conditions, these materials are mutually destructive and involve rapid degradation. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume well above threshold levels are a likely result. Unsafe pressurization of equipment such as extruder or mold can also result. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of halogenated materials from coming in contact with the acetal. Prevent contamination of virgin or rework resin.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Remarks - Oral:	No applicable toxicity data					
Remarks - Inhalation:	No applicable toxicity data					
Remarks - Dermal:	No applicable toxic	city data				
Titanium dioxide						
Remarks - Oral:	No applicable toxic	city data				
	LC50 Inhalation Rat - Male 6.82 Mg/l 4 h					
	LD50 Dermal Rabbit > 5,000 mg/kg -					
Conclusion/Summary	: Mixtu	re.Not fully tested.No	results available.			

Irritation/Corrosion



YELLOW K100

Version Number 1.0 Revision Date 04/08/2020 Page 10 of 17 Print Date 04/09/2020

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
Conclusion/Summary		•	•		·
Skin	: N	lixture.Not fu	lly tested.		
Eyes	: N	lixture.Not fu	lly tested.		
Respiratory	: N	lixture.			
<u>Sensitization</u>					
Conclusion/Summary					
Skin		lixture.Not fu	•		
Respiratory	: N	lixture.Not fu	lly tested.		
Mutagenicity					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
<u>Carcinogenicity</u>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		

Classification

Product/ingredient name	OSHA	IARC	NTP
Nickel antimony yellow	-	1	Known to be a human carcinogen.
rutile (C.I. Pigment Yellow			
53)			
Titanium dioxide	-	2B	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020

<u>PolyOne</u>

Page 11 of 17 Print Date 04/09/2020

Not available.		
Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the physical,	chemi	cal and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.
Delayed and immediate effects as <u>s</u> Short term exposure	well as	chronic effects from short and long-term exposure
	well as	<u>e chronic effects from short and long-term exposure</u> Not available. Not available.
<u>Short term exposure</u> Potential immediate effects	:	Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u> Potential immediate effects	:	Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u>	:	Not available. Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u> Potential immediate effects Potential delayed effects	::	Not available. Not available. Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u> Potential immediate effects Potential delayed effects	::	Not available. Not available. Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u> Potential immediate effects Potential delayed effects <u>Potential chronic health effects</u>	::	Not available. Not available. Not available. Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u> Potential immediate effects Potential delayed effects <u>Potential chronic health effects</u> Conclusion/Summary	::	Not available. Not available. Not available. Not available. Mixture.Not fully tested.No results available. No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Conclusion/Summary General Carcinogenicity	::	Not available. Not available. Not available. Not available. Mixture.Not fully tested.No results available. No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of exposure.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u> Potential immediate effects Potential delayed effects <u>Potential chronic health effects</u> Conclusion/Summary General	::	Not available. Not available. Not available. Not available. Mixture.Not fully tested.No results available. No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Conclusion/Summary General Carcinogenicity Mutagenicity	:::::::::::::::::::::::::::::::::::::::	Not available. Not available. Not available. Not available. Mixture.Not fully tested.No results available. No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of exposure. No known significant effects or critical hazards.

Numerical measures of toxicity

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020 Page 12 of 17 Print Date 04/09/2020

<u>PolyOne</u>

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure				
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)							
Remarks - Acute - Fish:	No applicable toxicity data						
Remarks - Acute - Aquatic	No applicable toxicity data						
invertebrates.:		XY 10 11 1 1 1					
Remarks - Acute - Aquatic	No applicable toxicity data						
plants:							
Remarks - Chronic - Fish:	No applicable toxicity data						
Remarks - Chronic -	No applicable toxicity data						
Aquatic invertebrates.:							
Titanium dioxide							
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h				
	water						
Remarks - Acute - Fish:	Acute		40.1				
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h				
Remarks - Acute - Aquatic	Acute	Crustaceans					
invertebrates.:							
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h				
		Daphnia					
Remarks - Acute - Aquatic	Acute						
invertebrates.:							
Remarks - Acute - Aquatic	No applicable toxicity data						
plants:							
Remarks - Chronic - Fish:	No applicable toxicity data						
Remarks - Chronic -	No applicable toxicity data						
Aquatic invertebrates.:							
YELLOW K100							
Remarks - Acute - Aquatic	Chemicals are not readily available a	as they are bound within the	e polymer matrix.				
invertebrates.:							
Conclusion/Summary		ly available as they are bou	nd within the				
	polymer matrix.						

YELLOW K100

<u>PolyOne</u>

Version Number 1.0 Revision Date 04/08/2020		Page 13 of 17 Print Date 04/09/2020
Persistence and degradability		
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.
<u>Bioaccumulative potential</u> Not available.		
Mobility in soil		
Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
		of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

YELLOW K100

<u>PolyOne</u>

Version Number 1.0 Revision Date 04/08/2020

Page 14 of 17 Print Date 04/09/2020

International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Nickel antimony yellow rutile (C.I. Pigment
	 Yellow 53) United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020

Print Date 04/09/2020

Page 15 of 17

1C.

:	Listed
:	Not listed
:	Not listed
	Not listed
•	
:	Not listed
	:

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
Titanium dioxide	>= 5 - <= 10	CARCINOGENICITY - Category 2
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	>= 5 - <= 10	CARCINOGENICITY - Category 1A

<u>SARA 313</u>

Form R - Reporting requirements

Product name	CAS number	%
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	>= 5 - <= 10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: The following components are listed:

YELLOW K100

Version Number 1.0 Revision Date 04/08/2020

PolyOne

Page 16 of 17 Print Date 04/09/2020

		Nickel antimony yellow rutile (C.I. Pigment Yellow 53) Titanium dioxide
Pennsylvania	:	The following components are listed: Nickel antimony yellow rutile (C.I. Pigment Yellow 53)
		, , , , , , , , , , , , , , , , , , ,

Titanium dioxide

California Prop. 65

WARNING: This product can expose you to chemicals including Nickel antimony yellow rutile (C.I. Pigment Yellow 53), Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	-	-
Titanium dioxide	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
<u>Inventory list</u>		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health

0

*



YELLOW K100

Version Number 1.0 Revision Date 04/08/2020 Page 17 of 17 Print Date 04/09/2020

Flammability	0
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Instor</u>		
Date of printing	:	04/09/2020
Date of issue/Date of revision	:	04/08/2020
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.