UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023



Page 1 of 18 Print Date 09/08/2023

SAFETY DATA SHEET

UV YELLOW TAG TPU II

Section 1. Identification		
GHS product identifier	:	UV YELLOW TAG TPU II
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	CC10324594
Product type	:	solid
· *		
Relevant identified uses of the subst	tance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
11		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)	•	accident).
(with nours of operation)		accident).


Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. Some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	ACUTE TOXICITY (inhalation) - Category 3 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

GHS label elements

UV YELLOW TAG TPU II



AVIENT

Page 2 of 18 Print Date 09/08/2023

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Causes serious eye damage. Toxic if inhaled. May cause cancer.
Precautionary statements		
Prevention Response	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing dust. IF exposed or concerned: Get medical advice or attention. IF
Response	•	INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.


Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10324594

CAS number/other identifiers

Ingredient name	%	CAS number
Chrome yellow (Lead chromate pigment)	>= 10 - <= 25	1344-37-2
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	>= 5 - <= 10	52829-07-9

UV YELLOW TAG TPU II





Page 3 of 18 Print Date 09/08/2023

Titanium dioxide	>-1 3	13463-67-7
Thainum dioxide	>= 1 = <= J	15-07-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023



Page 4 of 18 Print Date 09/08/2023

an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Inhalation Skin contact Ingestion	::	Causes serious eye damage. Toxic if inhaled. No known significant effects or critical hazards. No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness
		blistering may occur
Ingestion	:	Adverse symptoms may include the following: stomach pains
Indication of immediate medical atte	entio	n and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

ÀVIENT

Page 5 of 18 Print Date 09/08/2023

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containing	ment ai	nd cleaning up
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

ÀVIENT

Page 6 of 18 Print Date 09/08/2023

Large spill

disposal contractor.

:

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name

Exposure limits

6/18

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023



Page 7 of 18 Print Date 09/08/2023

Chrome yellow (Lead chromate pigment)	ACGIH TLV (2018-03-20) TWA 0.0002 mg/m3 (as Cr) Form: Inhalable fraction STEL 0.0005 mg/m3 (as Cr) Form: Inhalable fraction NIOSH REL (2010-09-01) TWA 0.0002 mg/m3 OSHA PEL 1989 (1989-03-01) CEIL 0.1 mg/m3 (as CrO3) OSHA PEL 1989 (1989-03-01) TWA 0.05 mg/m3 (calculated as Pb) OSHA PEL (2006-11-27) TWA 0.005 mg/m3 (as Cr) OSHA PEL (1993-06-30) TWA 0.05 mg/m3 (calculated as Pb) OSHA PEL Z2 (2006-11-27) CEIL 0.001 mg/m3
Decanedioic acid, bis(2,2,6,6- tetramethyl-4-piperidinyl) ester	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles

Appropriate engineering controls Environmental exposure controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measures				
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety		
		7/18		

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

ÀVIENT

	Page 8 of 18
7/2023	Print Date 09/08/2023

Eye/face protection	:	showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.	
Skin protection			
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.	

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Granular solid.]
Color	:	YELLOW
Odor	:	Not available.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not applicable.

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

ÀVIENT

Page 9 of 18 Print Date 09/08/2023

Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not applicable.
(flammable) limits		Upper: Not applicable.
Vapor pressure	:	Not available.
Vapor density	:	Not applicable.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not applicable.
octanol/water		
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
SADT		Not available.
Viscosity		Dynamic: Not available.
Viscosity	·	Kinematic: Not applicable.
<u>Aerosol product</u>		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	:	Not available.
equivalent		
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid Incompatible materials	:	Keep away from extreme heat and oxidizing agents. Keep away from strong acids.

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

AVIENT

Page 10 of 18 Print Date 09/08/2023

Hazardous decomposition products	:	Oxidizer. Under normal conditions of storage and use, hazardous decomposition products should not be produced. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). Do not use this pigment in polymers at temperatures over 200°C (392°F). Decomposition of diarylide pigments in polymers at temperatures over 200°C (392°F) may produce trace amounts of monoazo dyes, which in turn can decompose to produce aromatic amines. The amount and type of degradation products formed depend on the dwell time, formulation and processing conditions as well as temperature. As conditions become more severe, as when temperatures move into the 240-300°C (464-572°F) range, trace quantities of 3,3'-dichlorobenzidine can be generated. 3,3'- dichlorobenzidine is classified as a suspect carcinogen by NTP and IARC, is classified as Acute Toxicity category 4 and Carcinogen Category 1B according to 1272/2008EC (CLP), and is regulated by OSHA as a suspect carcinogen. In order to avoid the generation of and exposure to 3,3'-dichlorobenzidine, do not use diarylide pigments
		in polymers when temperatures exceed 200°C ($392^{\circ}F$). Handle with care. Organic dusts have the potential to be explosive with static spark or flame initiation.

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure		
Decanedioic acid, 1,10-bis(2,2,6,6-tetramethyl-4-piperidinyl) ester						
	LC50 Inhalation	Rat	0.5 Mg/l	4 h		
	Vapor		_			
Titanium oxide (TiO2)						
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	Dusts and mists		-			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		

Information on toxicological effects

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Conclusion/Summary		
Skin	:	Mixture.Not fully tested.
Eyes	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.

10/18

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

AVIENT

Page 11 of 18
Print Date 09/08/2023

Sensitization

Conclusion/Summary Skin Respiratory	:	Mixture.Not fully tested. Mixture.Not fully tested.
<u>Mutagenicity</u>		
Conclusion/Summary	:	Mixture.Not fully tested.
<u>Carcinogenicity</u>		
Conclusion/Summary	:	Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
C.I. Pigment Yellow 34	+	12A	Known to be a human carcinogen.Reasonably anticipated to be a human carcinogen.
Titanium oxide (TiO2)	-	2B	-

Reproductive toxicity

Conclusion/Summary	:	Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure) Not available. Specific target organ toxicity (repeated exposure) Not available. Aspiration hazard Not available.

Information on the likely routes of : Not available. **exposure**

Potential acute health effects

Eye contact	:	Causes serious eye damage.
Inhalation	:	Toxic if inhaled.
Skin contact	:	No known significant effects or critical hazards.

11/18

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023



Page 12 of 18 Print Date 09/08/2023

Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the physical, c	hemi	cal and toxicological characteristics
Eye contact Inhalation Skin contact Ingestion <u>Delayed and immediate effects and</u>	: : also c	Adverse symptoms may include the following: pain, watering, redness No specific data. Adverse symptoms may include the following: pain or irritation, redness, blistering may occur Adverse symptoms may include the following: stomach pains chronic effects from short and long term exposure
<u>Short term exposure</u> Potential immediate effects Potential delayed effects <u>Long term exposure</u>	:	Not available. Not available.
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General Carcinogenicity	:	No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity Teratogenicity Developmental effects Fertility effects	:	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
UV YELLOW TAG TPU II	150001.7 mg/kg	N/A	N/A	6.2 Mg/l	N/A
Decanedioic acid, 1,10- bis(2,2,6,6-tetramethyl-4-	N/A	N/A	N/A	0.5 Mg/l	N/A

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

Page 13 of 18 Print Date 09/08/2023

piperidinyl) ester					
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

:

Toxicity

Product/ingredient name	Result	Species	Exposure
Decanedioic acid, 1,10-bis(2,2,	6,6-tetramethyl-4-piperidinyl) ester		
	Acute EC50 8.6 Mg/l Fresh	Daphnia	48 h
	water		
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
		dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		

Not available.

Conclusion/Summary :

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
C.I. Pigment Yellow 34	-	3,600.00	high
Decanedioic acid, 1,10-bis(2,2,6,6-	0.35	-	low
tetramethyl-4-piperidinyl) ester			

Mobility in soil



Other adverse effects

Disposal methods

SAFETY DATA SHEET

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

ÀVIENT

Page 14 of 18 Print Date 09/08/2023

Soil/water partition coefficient : Not available. (KOC)

Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

No known significant effects or critical hazards.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: The following components are listed: Chrome yellow (Lead chromate pigment)
		14/10

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

ÀVIENT

Page 15 of 18 Print Date 09/08/2023

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Listed Chrome yellow (Lead chromate pigment) United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Chrome yellow (Lead chromate pigment) United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed Listed

Clean Air Act Section 112(b)	:
Hazardous Air Pollutants (HAPs)	
Clean Air Act Section 602 Class I	:
Substances	
Clean Air Act Section 602 Class II	:
Substances	
DEA List I Chemicals (Precursor	:
Chemicals)	
DEA List II Chemicals (Essential	:
Chemicals)	

Not listed

Not listed

Not listed

Not listed

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023

AVIENT

Page 16 of 18 Print Date 09/08/2023

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

ACUTE TOXICITY - inhalation - Category 3 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
C.I. Pigment Yellow 34	>= 10 - <= 25	CARCINOGENICITY - Category 1B
Decanedioic acid, 1,10- bis(2,2,6,6-tetramethyl-4- piperidinyl) ester	>= 5 - <= 10	ACUTE TOXICITY - inhalation - Category 1 SERIOUS EYE DAMAGE - Category 1
Titanium oxide (TiO2)	>= 1 - <= 3	CARCINOGENICITY - Category 2

<u>SARA 313</u>

Form R - Reporting requirements

Product name	CAS number	%
Chrome yellow (Lead chromate pigment)	1344-37-2	>= 7 - < 13

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations				
Massachusetts	: The following components are listed:			
	Calcium carbonate			
	Titanium dioxide			
	Silica, amorphous, precipitated and gel			
New York	: None of the components are listed.			
New Jersey	: The following components are listed:			
	Calcium carbonate			
	Chrome yellow (Lead chromate pigment)			
	Titanium dioxide			
	Silica, amorphous, precipitated and gel			
Pennsylvania	: The following components are listed:			
	Calcium carbonate			
16/18				

UV YELLOW TAG TPU II

Version Number 1.2 Revision Date 09/07/2023



Page 17 of 18 Print Date 09/08/2023

Chrome yellow (Lead chromate pigment)

Titanium dioxide

Silica, amorphous, precipitated and gel

California Prop. 65

.

WARNING: This product can expose you to chemicals including Chrome yellow (Lead chromate pigment), which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable	
		dosage level	
Chrome yellow (Lead chromate pigment)	Yes.	Yes.	
Titanium dioxide	-	-	

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations Inventory list		
Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
		Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

Section 16. Other information

4 11

Hazardous Material Information System (U.S.A.)

UV YELLOW TAG TPU II



Version Number 1.2 Revision Date 09/07/2023

Page 18 of 18 Print Date 09/08/2023

Health	*	3
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>History</u>		
Date of printing	:	09/08/2023
Date of issue/Date of revision	:	09/07/2023
Date of previous issue	:	07/30/2021
Version	:	1.2
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.